

DIN 46391

d1	d2	d4	d5 Hole or pin	e	l1	l2	Winding volume [dm <sup>3</sup> ]															
710	355	80	30	100	550	400	119															
800	400		40				151															
900	450		50				160	900	710	560	267											
1000	500										330											
1250	630										650											
1400	710										812											
1600	800										1357											
1800	1000										1583											
2000	1000										300	400	1120	900	1360	2638						
	1250															2144						
1120	1360	1120		3309																		
2240	1400	1450		1220	2928																	
	1250	1360	1120	4121																		
2500	1400	400	1450	1220	1690	1380	4109															
	1600						3534															
1800	4983																					
2800	1800						7238															
3000	2000						6283															
3150	1800						140	65	600	2000	1600	8397										
	2000											7442										
3390	2000											65	600	2000	1600	8837	9076					
	2360																7103					
2000	10810																					
3550	2360	200	80	600	2000	1600											8837					
	2650																12006					
3750	2650																80	1000	2500	2000	2000	9952
	2650																					12691
4000	2800																					200
	2650						17341															
4250	2800						80	1000	2500	2000	2000											
	2800											19493										
4500	3000											17671										

DIN 46395

d1	d2	d3	d4	d5 Hole or pin	e	l1	l2	Winding volume [dm <sup>3</sup> ]																								
315	125	71	36	8 bis 16	71	236	200	13																								
	160							190	160	9																						
	140							265	224	19																						
355	180							112	56	16 bis 32	140	375	315	52																		
	160													300	250	26																
400	200													160	80	28 bis 40	160	850	710	525												
	180																			335	280	52										
450	224																			200	100	40 bis 63	300	1900	1600	5027						
	200																									375	400	105				
500	250																									280	140	280	1800	2120	1800	6503
	224	425	355	73																												
560	280	160	80	40 bis 63	300	1700	1400																									3799
	250																															475
630	315							160	80	28 bis 40	160	1060	900																			1029
	315																															530
710	355													200	100	40 bis 63	300	1500	1250													2696
	400																															600
800	450																			250	125	40 bis 63	300	1700	1400							3799
	500																															670
900	500																									280	140	40 bis 63	300	1900	1600	5027
	550																															750
1000	500	280	140	40 bis 63	300	2120	1800																									6503
	550																															850
1120	560							280	140	40 bis 63	300	2120	1800																			6503
	630																															950
1250	630													280	140	40 bis 63	300	2120	1800													6503
	710																															1060
1400	710																			280	140	40 bis 63	300	2120	1800							6503
	800																															1180
1600	800																									280	140	40 bis 63	300	2120	1800	6503
	850																															1320
1800	1000	280	140	40 bis 63	300	2120	1800																									6503
	1000																															1500
2000	1120							280	140	40 bis 63	300	2120	1800																			6503
	1250																															1700
2240	1250													280	140	40 bis 63	300	2120	1800													6503
	1500																															1900
2500	1500																			280	140	40 bis 63	300	2120	1800							6503
	1800																															2120

DIN 46397

d1	d2	d3	d4	l1	l2	d5 Hole or pin	e	t1	t4	t5	Winding volume [dm <sup>3</sup> ]																		
160	90	80	118	95	-	-	40	13	1	1	1																		
	112										3																		
	125										2																		
200	140										100	150	118	-	-	50	16	2	2										
	125																		4										
140	3																												
224	160																		100	170	140	-	-	50	16	2	3		
	140																										5		
160	5																												
250	180																										160	127	190
	180	11																											
200	9																												
315	224	160	127	236	200	-	-	50	16	2																			
	200										12																		
200	15																												
355	250										160	127	265	224	16	100	63	20											
	224																		17										
224	22																												
400	280																		160	127	300	250	-	-	63	20			
	250																										16		
250	25																												
450	315																										160	127	355
	280	27																											
280	23																												
500	355	160	127	375	315	-	-	63	20	2																			
	315										34																		
315	43																												
560	400										160	127	425	355	-	-	63	20											
	355																		31										
355	47																												
630	450																		160	127	475	400	28	100	63	20			
	400																										52		
450	43																												
710	500																										300	250	530
	450	86																											
450	74																												
800	560	300	250	600	500	40	170	125	40	3																			
	560										61																		
630	96																												
1000	710										200	250	750	630	-	-	125	40											
	800																		122										
800	107																												
1250	900																		300	250	950	800	50	250	125	40			
	710																										137		
800	172																												
1250	900																										300	250	950
	710	128																											
800	340																												
1250	900	300	250	950	800	50	250	125	40	3																			
	710										245																		
800	665																												
1250	900										300	250	950	800	50	250	125	40											
	710																		473										

